

SAFETY DATA SHEET

SECTION 1 IDENTIFICATION

PRODUCT

Product Name: Odourless Solvent
Product Description: Isoparaffinic Hydrocarbon
Intended Use: Solvent

COMPANY IDENTIFICATION

Supplier: Demco Encouleurs Inc.
 3417 1^{ere} Rue
 St. Hubert , Quebec
 J3Y 8Y6 Canada

Preparation date of MSDS: 5 /April/2018

Product Technical Information 450-443-8455

SECTION 2 HAZARD IDENTIFICATION

Potential Acute Health Effects:

Eye Contact: May cause mild eye irritation. May cause mild discomfort.

Skin Contact: May cause mild skin irritation. Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis.

Inhalation: Excessive exposure may cause irritation of the eyes, upper respiratory tract (nose and throat) and lungs.

Ingestion: Low toxicity. Aspiration into the lungs may occur during ingestion or vomiting, resulting in lung injury.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Name	CAS#	Concentration*	LD50s and LC50s Route & Species:
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	64742-48-9	60-100%	Dermal LD50 Rabbit > 3160 mg/kg Oral LD50 Rat > 5000 mg/kg Inhalation, aerosol, 4hr LC50 Rat >2.5 g/m3

SECTION 4	FIRST-AID MEASURES
------------------	---------------------------

Eye Contact: Flush eyes with large amounts of water until irritation subsides. If irritation persists or signs of toxicity occur, seek medical attention.

Skin Contact: Flush skin with large amounts of water. If irritation persists, get medical attention.

Inhalation: Move person to fresh air. Administer artificial respiration if breathing has stopped. Allow victim to rest in a well-ventilated area. Seek immediate medical attention

Ingestion: Do not induce vomiting. Seek immediate medical attention.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis.

SECTION 5	FIRE-FIGHTING MEASURES
------------------	-------------------------------

Flash Point: 38 °C / 100.4 °F

Flash Point Method: Tag Closed Cup

Autoignition Temperature: 246°C /475°F

Flammable Limits in Air (%): Lower: 0.7% Upper: 5.3%

Extinguishing Media: Use DRY chemicals, CO2, alcohol foam or water spray.

Special Exposure Hazards: Combustible. May release vapors that form flammable mixtures at or above the flash point.

Use water spray to cool fire-exposed containers and structures. Shut off fuel to fire. Avoid spraying water directly into storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Hazardous Decomposition/Combustion Materials (under fire conditions): Carbon monoxide. Carbon dioxide.

Special Protective Equipment: Fire fighters should wear full protective clothing, including self-contained breathing equipment.

NFPA RATINGS FOR THIS PRODUCT ARE: HEALTH 1, FLAMMABILITY 2, INSTABILITY 0

HMIS RATINGS FOR THIS PRODUCT ARE: HEALTH 1, FLAMMABILITY 2, REACTIVITY 0

SECTION 6**ACCIDENTAL RELEASE MEASURES**

Personal Precautionary Measures: Wear appropriate protective equipment.

Environmental Precautionary Measures: Prevent entry into sewers or streams, dike if needed. Consult local authorities.

Procedure for Clean Up: Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapour-suppressing

foam may be used to reduce vapour. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapour, but may not prevent ignition in enclosed spaces. Recover by pumping or with suitable absorbent.

Water Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Do not confine in area of spill. Advise occupants and shipping in downwind areas of fire and explosion hazard and warn them to stay clear. Warn other shipping. Allow liquid to evaporate from the surface. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken. If the flash point exceeds the ambient temperature by 10 °C or more, use containment booms and remove from the surface by skimming or with suitable absorbents when conditions permit. If the flash point does not exceed the ambient air temperature by at least 10 °C, use booms as a barrier to protect

shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.

SECTION 7**HANDLING AND STORAGE**

Handling: For industrial use only. Handle and open containers with care. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid inhalation of chemical. DO NOT handle or store near an open flame, heat, or other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. DO NOT pressurize, cut, heat, or weld containers. Empty containers may contain hazardous product residues. Keep the containers closed when not in use. Protect against physical damage. Use appropriate personnel protective equipment. Handling Temperature: Ambient. Static Accumulator: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semi conductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

Storage: Store in a cool, dry, well ventilated area, away from heat and ignition sources. Place away from incompatible materials. Store in accordance with good industrial practices. Store at ambient temperature. Suitable

Containers/Packing:

Drums; Barges; Tank Cars; Tank Trucks

Suitable Materials and Coatings: Carbon steel; Teflon; Stainless steel;

Unsuitable Materials and Coatings: Polystyrene; Natural rubber; Butyl rubber; Ethylene-propylene-diene monomer (EPDM)

SECTION 8	EXPOSURE CONTROLS / PERSONAL PROTECTION
------------------	--

EXPOSURE LIMIT VALUES

Substance Name	Exposure Limit - ACGIH Form	Exposure Limit - OSHA	Immediately Dangerous to Life or Health - IDLH Source
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Manufacturer Recommends: a TWA of 1200 mg/m ₃ (175 ppm) based on total hydrocarbon. Local regulated limits may vary.	. Not available	Not available

Engineering Controls:

Use process enclosure, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. Use explosion proof equipment.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator. For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filters capacity/rating may be exceeded.

Gloves: Appropriate chemical resistant gloves should be worn. If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with forearms is likely, wear gauntlet-style gloves. The breakthrough time of the selected glove(s) must be greater than the intended use period.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials as well as the instructions/specifications provided by the glove supplier.

Skin Protection: Skin contact should be prevented through the use of suitable protective clothing, gloves and footwear, selected for conditions of use and exposure potential. Consideration must be given both to durability as well as permeation resistance.

Eyes: Chemical safety glasses with side shields or splash proof goggles.

Other Personal Protection Data: Ensure that eyewash stations and safety showers are proximal to the work-station location.

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

Odor : Odorless

Physical State: Liquid

Color: Clear Colorless

pH Not Available.

Specific Gravity: 0.763 @ 15.6°C

Boiling Point: 182-204°C / 360-399°F

Freezing/Melting Point: <-78°C / <-108°F

Vapor Pressure: 0.09 kPa @ 20°C

Vapor Density: 5.6 @ 101 kPa

% Volatile by Volume: 100%

Evaporation Rate: 0.09

Solubility: Negligible in water.

VOCs: 763 g/l @ 15°C; 6.359 lbs/gal (EPA method 24)

Viscosity: 1.84 cST @ 25 C

Molecular Weight: 162

SECTION 10	STABILITY AND REACTIVITY
-------------------	---------------------------------

Chemical Stability: Stable.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid excessive heat, open flames and all ignition sources.

Materials to Avoid: Strong oxidizing agents.

Hazardous Decomposition Products: Material does not decompose at ambient temperatures.

Additional Information: No additional remark

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

Principle Routes of Exposure

Ingestion: Low toxicity. Aspiration into the lungs may occur during ingestion or vomiting, resulting in lung injury.

Skin Contact: May cause mild skin irritation. Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis.

Inhalation: Excessive exposure may cause irritation of the eyes, upper respiratory tract (nose and throat) and lungs.

Eye Contact: May cause mild eye irritation. May cause mild discomfort.

Additional Information: Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized. For the product itself: Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death. Prolonged and/or repeated skin contact with low viscosity materials may

defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Acute Test of Product:

Acute Oral LD50: Not Available.

Acute Dermal LD50: Not Available.

Acute Inhalation LC50: Not Available.

Carcinogenicity:

Carcinogenicity Comment: No additional information available.

Reproductive Toxicity/ Teratogenicity/ Embryotoxicity/ Mutagenicity: Not Available.

SECTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

Ecotoxicological Information:

Chemical Name	Ecotoxicity - Fish Species Data	Ecotoxicity - Freshwater Algae Data
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	2200 mg/L LC50 (Pimephales promelas)96 h	Not Available.

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

Disposal of Waste Method: Disposal of all wastes must be done in accordance with municipal, provincial and federal regulations.

Contaminated Packaging: Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

DOT (U.S.):
DOT Shipping Name: PETROLEUM DISTILLATES, N.O.S.
DOT Hazardous Class 3
DOT UN Number: UN1268
DOT Packing Group: III
DOT Reportable Quantity (lbs): Not Available.

Note: No additional remark.

Marine Pollutant: No.

TDG (Canada):

TDG Shipping Name: PETROLEUM DISTILLATES, N.O.S.

Hazard Class: 3

UN Number: UN1268

Packing Group: III

Note: Not regulated under the Transportation of Dangerous Goods Act when transported by road or rail in packagings or containers of 450 L or less (waste excluded).

Marine Pollutant: No.

SECTION 15	REGULATORY INFORMATION
-------------------	-------------------------------

U.S. TSCA Inventory Status: All components of this product are either on the Toxic Substances Control Act (TSCA) Inventory List or exempt.

Canadian DSL Inventory Status: All components of this product are either on the Domestic Substances List (DSL), the Non-Domestic Substances List (NDSL) or exempt.

U.S. Regulatory Rules

Chemical Name	CERCLA/SARA – Section 302	CERCLA/SARA – Section 313	SARA (311, 312) Hazard Class
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Not Listed.	Not Listed.	Not Listed.

California Proposition 65: Not Listed.

MA Right to Know List: Not Listed.

New Jersey Right-to-Know List: Not Listed.

Pennsylvania Right to Know List: Not Listed.

Additional Notes: Not Available.

WHMIS Hazardous Class:

B3 COMBUSTIBLE LIQUIDS



SECTION 16	OTHER INFORMATION
-------------------	--------------------------

Additional Information: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Disclaimer: NOTICE TO READER:

Univar, expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a Product

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Demco Encouleurs makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Demco Encouleurs's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

*****END OF MSDS*****